

## IM10T Drop Weight Impact Testers



A highly versatile range of drop weight impact testers for performing a wide range of medium energy tests on materials, specimens and end products of various geometry.

- Laboratory grade instrumentation and very rigid construction for highest accuracy test results.
  - Guided mass system to ensure that the impact geometry is correct throughout the test.
  - Highly accurate and repeatable drop parameters.
  - Very robust construction stands up to the rigours of dynamic testing to provide high reliability with a minimum of downtime.
  - Easily interchangeable contact parts simplify maintenance and reduce cost of ownership.
- Very high levels of safety employing multiple redundant systems, compliant with 89/392/EEC and 91/368/EEC machinery safety directives.
  - High quality, easy to use control and analysis software ensures consistency and enhances throughput.
  - Simple service requirements of single phase mains electricity and compressed air reduce installation costs.
  - Multiple impact facility for fatigue testing.
  - Wide range of strikers, anvils, fixtures and jigs available for standard test geometries, and for custom testing.
  - Optional sample strippers for extracting striker from tough ductile specimens.
  - Optional second impact prevention system for non-penetrating tests.
  - Optional high velocity impact option for impact velocities up to 20m/s.
  - Optional dynamic displacement measurement system for direct measurement of the sample deformation.
  - Optional high speed, fully integrated video system to provide visualization of specimen failure mode.
  - Optional temperature conditioning chamber, -70°C to +200°C.
  - Responsive life-time technical support.

### Product Range

- IM10T-20** impact energy up to 600J requiring a floor-to-ceiling height of 4.5m (5kg to 30kg impact mass at 1.0m/s to 6.26m/s impact velocity)
- IM10T-25** impact energy up to 750J requiring a floor-to-ceiling height of 5.0m (5kg to 30kg impact mass at 1.0m/s to 7.0m/s impact velocity)
- IM10T-30** impact energy up to 900J requiring a floor-to-ceiling height of 5.5m (5kg to 30kg impact mass at 1.0m/s to 7.7m/s impact velocity)

Custom drop heights, High Velocity and a high mass option up to 100kg available